


MIG200 PFC



Features:

- Rugged, robust, and industrial look with ergonomic design
- **ClearVision** Technology
- **Intelligent synergic control**
- Adaptable wide voltage range
- Welding engineer mode
- **Smart Lift TIG**
- Consistent and efficient MIG spot welding performance
- Flexible remote control solutions
- Power factor correction (PFC), generator-friendly
- Quick factory reset; auto sleep mode
- Compatible with MIG digital torch and spool gun
- LED inside wire feeder cabinet; handy accessory storage slot
- **ABAP: Active Balancing Air Passage**
- On demand fan
- Voltage Reduction Device (VRD)
- Key power electronic component protection
- Overcurrent and overheat protection



Specifications:

		MIG200 PFC N2S62	
Input power		AC95~265 V, 50/60 Hz	
Open circuit voltage		67 V	
MIG	Rated input current	41.8 A	38.3 A
	Rated input power capacity	3.68 kVA	5.74 kVA
	Output current range	30~140 A	30~200 A
	Rated duty cycle	25%	
	Wire feed speed	2~13 m/min	2~15 m/min
	Wire spool size	D200	
MMA	Rated input current	28.5 A	25 A
	Rated input power capacity	3.28 kVA	5.77 kVA
	Output current range	20~110 A	20~180 A
TIG	Rated input current	23.7 A	19.1 A
	Rated input power capacity	2.79 kVA	4.43 kVA
	Output current range	5~140 A	5~200 A
	Rated duty cycle	25%	
Efficiency	84%		
Power factor	0.99		
Idle state power	<50 W		
Protection class	IP23S		
Insulation class	H		
Dimensions L×W×H	565×220×415 mm		
Net weight	16 kg		



Standard Accessories

- 3M MB-15 MIG torch
- 3M earth clamp
- 1 pc quick socket
- 2 pcs hose clamps

